

DELO®-PRE 4003

Primer for Acrylates, DELO-PHOTOBOND

Base

- silane

Use

- for the pretreatment of bonding surfaces to improve the long-term resistance of bondings exposed to increased stress through humid warmth
- for the bonding of glass with DELO-PHOTOBOND adhesives
- suitable in combination with all DELO-PHOTOBOND adhesives

Processing

- the surfaces to be bonded must be dry as well as free of dust, grease and other contaminations
- shake primer before use
- preferable primer application by brushing, dipping or spraying the bonding surfaces
- a great advantage of DELO-PRE 4003 is that pretreated materials can still be bonded several hours after primer application, contamination-free storage provided
- container must be stored closed

Technical data

Color colorless clear

Evaporation time [s] approx. 60
at room temperature (approx. 23 °C)

Storage life 1 year
at room temperature (approx. 23 °C) in unopened original container

DELO Industrial Adhesives LLC
400 Oser Ave., Suite 1650
Hauppauge, NY 11788
Phone 781 373 5705
Fax 781 373 3705
info@DELO.us · www.DELO.us

Instructions and advice

General

The data and information provided are based on tests performed under laboratory conditions. Reliable information about the behavior of the product under practical conditions and its suitability for a specific purpose cannot be concluded from this.

Many product properties are subject to temperature and may change permanently, especially at high temperatures.

It is the user's responsibility to test the suitability of the product for the intended purpose and temperature range of use by considering all specific requirements. Type and physical and chemical properties of the materials to be processed with the product, as well as all actual influences occurring during transport, storage, processing and use, may cause deviations in the behavior of the product compared to its behavior under laboratory conditions. All data provided are typical average values or uniquely determined parameters measured under laboratory conditions.

The data and information provided are, therefore, no guarantee for specific product properties or the suitability of the product for a specific purpose.

Occupational health and safety

see material safety data sheet

Specification

see quality assurance test report

Converting table

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$

$\text{mm} / 25.4 = \text{inches}$

$\mu\text{m} / 25.4 = \text{mil}$

$\text{g} / 28.3495 = \text{oz.}$

$\text{Mpa} \times 145 = \text{psi}$

$\text{mPas} = \text{cP}$

$\text{N} \times 0.225 = \text{lb.}$